

2Megapixel HD IP Camera for Home



- ※ 1/3" inch 2.0MP CMOS
- ※ 1/4" inch 1.0MP CMOS
- ※ 3.6MM Fixed Lens;
- ※ IR View Distance:8-10m(12pcs leds);
- ※ H.264 Codet;
- ※ Plug & Play;
- ※ Video & Push;
- ※ WPS & AP Function;
- ※ Real- Time Frame: Rate: 30fps Max;
- ※ Power Supply 5V/2A
- ※ Onvif Compatibility;
- ※ Wifi 802.11 b/g/n

Specification

Model	WS-IP005	WS-IP005S
Device Type	1.0 Megapixel CMOS Sensor	2.0 Megapixel CMOS Sensor
Size	1/4"	1/3"
Day & Night		Yes
Color		0.5Lux (IR ON)
IR Cut		Support
Filter		IC-CUT Filter
IR Led		Yes
IR Distance		8-10M
Lens		
Lens		3.6MM
IRIS		Fixed Aperture F1.2
Viewing Angle		Pan:355° Tilt: 90°
Video		
Compression		H.264
Resolution & Frame	Main Flow: 1280x720@30fps; Minor Flow: 640x360@30fps	Main Flow: 1920x1080@15fps,1280x720@30FPS; Minor Flow: 640x360@30fps
Code Stream		Support Dual Stream
Code Rate		32-4096kbps
Bit Rate Type		CBR & VBR
SNR		Above 50DB
Image Enhancement	Automatic White Balance, Backlight Compensation, Luminance, Contrast, Color Adjustment	
Video Cover		4 Region can be set up
Superposition of Words		User Defined
Flip Config		Up/Down, Left-right-flip
Alarm		
Audio		Two-way-audio
Device		Built-in Mic External Output Device
Audio IN/Out		1CH
Audio Compression		G.711/G.726
Alarm Way		Motion Detection
Alarm Procession	The central control monitor, Got to PTZ preset pos, Send E-mail, Log Record, SD Card storage, etc.	
Protocol & Service	TCP,UDP,IP,HTTP,SMTP,DHCP,DNS,DDNS,ARP,ICMP,SMTP,POP3,NTP,RTP,RTCP,Pelco-D	
Ethernet Port	Ethernet(10/100 Base-T),RJ-45 conector	
Security	IP Address Filter, User Password Protection, User Access Log	
WEB Browser	Microsoft Internet Explorer 6.0 or above, google, firefox, etc.	
Software Management	Multi-channel Network Surveillance System ONVIF Compatibility	
Intelligent Software Function	Motion Detect, Miss Object Detection, Suspicious Detection, Moving Object Tracking, Guard Line Detection, etc.	
Event Action	Video Capture Saved to Backing Device, Send Email, Send SMS,Zoom in alarm, Pop ap map, Go to PTZ preset pos etc.	
Mobile Client	Iphone,Android	
Remote Access	DDNS, Software, P2P	
General		
Accessories	Power adapter, Network Cable, Stand, User Manual, Disk, Screw Bag	
Power Consumption	DC 5V/2A	
Operation Temperature	-10°C——60°C	
Operation Humidity	10% -80%	
Weight	0.5kg	
Dimension	103 x 75 x 124mm(L x W x H)	
Certification	CE,FCC.	

※※※Product specification are subject to change without notice ※※※

www.winsafecctv.com