





AMC-E200U2 (12X , 72.5° FOV)
AMC-E210U2 (10X , 60.9° FOV)



Features

- ※ UP to 72.5°FOV
- ※ USB 2.0 interface,MJPEG compression
- ※ Support standard UVC protocol
- ※ With OSD menu,support image flip
- ※ Come with IR remote controller
- ※ Support standard VISCA & Pelco communication protocols
- ※ RS232IN/IR RS232OUT/RS485 control interface,support daisy chain
- ※ Special mechanical PTZ driving system,ensure precise positioning
- ※ Provide an extra DVI-D video interface
- ※ UP to 12X Optical zoom,12X digital zoom
- ※ UP to 1080p30 HD video format

Dimensional Drawing



- | | |
|---------------|-------------------|
| ① USB2.0 | ④ RS-232OUT/RS485 |
| ② DVI-D | ⑤ DC12V |
| ③ RS-232IN/IR | |

Technical Specification

Model No.	AMC-E200U2	AMC-E210U2
Image Sensor	1/2.8" Exmor CMOS, 2.14MP	
Video Standard(HD)	USB2.0 (MJPEG) 1080/30,720p/50,720p/30,640x480p/30	
Focal	f = 3.9mm -46.8mm	f=4.7mm-47mm
IRIS	F1.6 - F2.8	F1.6 - F3.0
Zoom	Optical: 12X, Digital: 12X	Optical: 10X
Field of View	72.5° - 6.3°	
Focus	Auto, Manual, PTZ Trigger AF, One push	
Min.Illumination	0.5Lux(Color), 0.1Lux(B/W)	
Shutter Speed	1/1 - 1/10,000s	
AGC	Auto/Manual	
White Balance	Auto, Indoor, Outdoor, One push, Manual, Automatic Tracking,Sodium,Fluorescent	
AE Control	Auto, Manual, Shutter Priority, Iris Priority,Intelligence	
WDR	Yes	
BLC	Yes	
Noise reduction	2D/3D	
PTZ		
Pan Range	-170° - +170°	
Tilt Range	-30° - +90°	
Pan Speed	0.1° - +120°/s	
Tilt Speed	0.1° - +80°/s	
Preset Number	256	
OSD	Yes	
Image Flip	Yes	
Interface		
Video Output	USB2.0,DVI-D	
Control Interface	USB2.0,RS-232IN/IR, RS-232OUT/RS-485	
General		
Control Protocol	VISCA and Support Daisy Chain, PELCO-D, PELCO-P	
Address	0 - 63	
Power Supply	DC12V	
Working Temp	0°C - +40°C	
Storage Temp	-20°C - +60°C	
Dimension	243mm x 145mm x 163mm	
Weight	1.2KG	
Color	Grey	
Product specification are subject to change without notice		