



Features

- ※ 1/2.8" SONY Starvis Back-illuminated CMOS Sensor
- ※ 2MP 1080P HD hidden camera
- ※ POE optional
- ※ Support WIFI and Onvif 2.4, control at iPhone, iPad, Android, Android Pad.
- ※ DC 12V $\pm$ 10%

Technical Specification

Model NO.	WS-LW06
Camera	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Resolution	2MP 1080P
Effective Pixels	1945(H)*1097(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	$\geq$ 52dB
Scanning System	Progressive
Video Output	Network
Reset Button	\
LENS Type	
Focus Length	Board Lens 3.7mm/F2.8
Focus Control	Fixed
Lens Type	Fixed
Pixels	3Mp
Night Vision	
Infrared LED	/
Infrared Distance	/
IR Status	/
IR Power On	/
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Optional(External POE But Without Audio and Alarm Functions), Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	1920*1080@30fps
Main Stream 2	1280*720@25fps
Main Stream 3	/
Sub Stream 1	720*480@30fps

Sub Stream 2	/
Sub Stream 3	/
Tri Stream	352*288@30fps
IE Brower	IE9-11, Google Chrome(Under Ver 45), Firefox(Under Ver 53), Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad
Wireless	
Antena	2.5dbi
Hotspot	/
Wi-Fi	Wi-Fi(IEEE802.11b/g/n),2.4Ghz
WIFI Range	No obstacles 100m Max.
Function	
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Corridor Pattern	Support
ROI	/
Defog Mode	Support
BLC	Support
HDR	/
WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/NAS/VMS/Web/SD Card
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese
Interface	
Audio	2-way audio(3.5mm audio interface)
Alarm	1channel Input(5V~20V)
SD Card Slot	support 128G Micro SD
RS485	/
General	
Housing	Metal
Anti-cut Bracket	YES
IR Cut Filter	NO
Operation Temperature	-20℃~60℃ RH95% Max
Storage Temperature	-20℃~60℃ RH95% Max
Power Source	DC12V±10%, 550mA
Dimension	36(W) x 36(H) x27(D)mm
Weight	300g
***Product specification are subject to change without notice ***	