

560TVL WDR Dome Camera(WS-WR003)



Features

- ※ 60dB Dual Scan WDR
- ※ Color 560TVL Hi Resolution
- ※ Full Function 14 Language OSD Menu
- ※ RS-485(PELCO-D/P) Remote Control
- ※ AC24V/DC12V Dual Power
- ※ Video,Power,RS485 Thunder Proof
- ※ 3D-DNR Function
- ※ Motion Detection Alarm Output
- ※ Shutter Speed Adjustable
- ※ Privacy Zone Masking
- ※ Electronic Image Stabilizer
- ※ Digital Zoom x8
- ※ Line Lock Function
- ※ A/B/C Lens Option



A:3.7~12mm



B:9~22mm



C:6~50mm

Specification

Model No.	WS-WR003N	WS-WR003P
Line Scan Frequency	15.734kHz	15.625kHz
Filed Scan Frequency	59.94Hz	50.00Hz
Effective Pixels	768(H) x 494(V)	752(H) X 582(V)
Electronic Shutter	1/60 - 1/90,000sec	1/50 - 1/90,000sec
Sensor	SONY vertical double-density interlind 1/3" CCD	
Scan Mode	2:1 Interlace Scan	
Resolution	560TVL Lines(Color) / 620TVL Lines(B/W,Signal Enhancement)	
illumination	0.2Lux at F1.2(Color Mode)/0.05Lux at F1.2(B/W Mode)/0.0002Lux at F1.2(Sense Up Mode)	
S/N Ratio	54dBMin.(AGC OFF)	
Iris Control	DC AUTO IRIS(Shutter speed 1/50 - 1/90,000)ELC	
Communication Mode	RS485, PELCO D/P	
AWB	Indoor/Outdoor/Manual Modes	
WDR	ON/OFF	
SYNC, Mode	INT./EXT. 2 Modes	
Privacy Masking	ON/OFF(8 Areas for Option)	
Motion Detect Alarm	ON/OFF(4 Areas for Option)	
Mirror	OFF/H-MIRROR/V-MIRROR/ROTATION FOR OPTION	
AGC	OFF/LOW/MIDDLE/HI OPTIONAL	
Sense Up	OFF/1X-128X	
D/N Mode	Auto/Day/Night/EXT.Control for option	
D-Zoom	1x - 8x	
Video Signal	1.0Vp -p/75Ω Video,0.714Vp-p Composite,0.286Vp-p	
Lens	A:TAMRON Lens:f=3.7-12mm,F=1:1.4 ICR DC Auto IRIS B:CANON Lens:f=9.0 - 22mm,F=1:1.4 ICR DC Auto IRIS A:KAWADEN Lens:f=6.0 - 50mm,F=1:1.4 ICR DC Auto IRIS	
Power Supply	12VDC/24VAC Dual Power Supply	
Power Consumption	2.8W(AC), 2.6W(DC)	
Size	141(D) x 105(H) mm	
Storage Temperature	-40 ℃ - +60℃	
Operation Temperature	- 10 ℃ - +50℃	
Humidity Range	20%-90%	
Weight	700g	

※※※Product specification are subject to change without notice ※※※