

NVR Kits(WS-NVK-803)



Features

- ※ It can connect with IP camera and network video server, **support Onvif, P2P,Video push**;
- ※ Live view, record, search file, backup, playback (4ch playback Syn)
- ※ Digital zoom (both in live view and playback)

Parameter

Model No.		WS-NVK-803
OS		embed LINUX
Date Rate		Adjustable
Dual Stream		Supprt
Resolution		1080P(1920x1080)30fps/960P(1280x960)/720P(1280x720)30fps
Motion detection		Multiple zone detection, 1-6 sensitivity adjustable(IPC match)
Playback		4ch 960P/720P,10.5LCD
Privacy Zone		4 zone for each IPC(IPC match)
Record mode		Manual, Auto, MD, Alarm(IPC match)
Backup		Local HDD、 U-disk, removable HDD, DVR-RW, network storage
Operate mode		Mouse
Login		User name and password
Storage		Local and network
Interface	Video input	4x(1280 * 720) IP Camera or 4x(1280 * 960) IP Camera
	Audio input	4 IP Audio input
	Video output	1VGA +HDMI
	Audio output	1 RCA
	Network interface	1 RJ45, 10M/100Madaptive Ethernet Interface
	RS485 port	Standard 485 port
	USB Port	2 USB 2.0 port
	Wireless	3G
HDD	Interface type	1 SATA interface
	Capacity	Up to 3TB capacity for each disk
Mobile phone monitoring		Support(iPhone, Windows Mobile, BlackBerry, Symbian, Android)
Power Supply		12V,2.6A
Consumption		≤25(without HDD)
Working Temperature		-10℃ ~ +55℃
Working Humidity		10% - 90%
Dimension		NVR: 260mm x 220mm x 43mm; Packing: 355mm x 255mm x 88.5mm
Weight(without HDD)		Net:1.5kg; Gross:2.4kg

Camera

Image Sensor	1/4" Progressive Scan CMOS
Signal System	PAL/NTSC
Min. illumination	Color 1 Lux @ (F1.2); B/W 0.1Lux@(F1.2),0 Lux with IR
Lens	3.6/4/6mm 36pcs IR Lens
Day & Night	IR Cut Filter with auto switch
Compression Standard	
Video Compression	H.264
Bit Rate	0.1Mbps - 6Mbps
Dual Stream	Yes
Image	
Max. Image Resolution	1280 x 720
Frame Rate	30fps(1280 x 720)
Image Settings	Saturation, brightness, contrast adjustable through client software or web browser, Backlight compensation, Backlight compensation
Network	
Alarm Trigger	Motion detection, Tampering alarm
Protocols	RTSP/FTP/PPPoE/DHCP/DDNS/NTP/UPnP
Security	User authentication
System Compatibility	ONVIF 2.0, P2P, Video Push
Interface	
Communication Interface	1 RJ45 10M/100M ethernet interface
General	
Operating Conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F);Humidity 95% or less (non-condensing)
Power Supply	12 VDC ± 10%
Power Consumption	Max. 5W(Max. 7W with IR cut filter on)
IR light	ø 5 24pcs IR light
Dimension	100 x 70 x 60 mm
Weight	500g

Product specification are subject to change without notice

www.winsafecctv.com