

1080P Low Lux Plastic IR Dome IP Camera



Specification	
Model	WS-IP307
Item	Plastic Dome Camera
Device Type	1080P Sony MX 122 CMOS Sensor
Size	1/2.5
Day/Night	Yes
Min. Scene Illumination	0.01Lux(IR ON)
Infrared Sensitivity	Support
Filter	IR-CUT
IR-led	Yes
IR Distance	15-20M
Electronic Shutter	1/5-1/15,000/s
lens	
Lens	3.6MM Lens optional
Aperture	Fixed Aperture F1.2
Video	
Compression	H.264 Main Profile/Baseline
Picture Resolution	1920x1080@30fps
Steam flow	Suport dual stream
Bit Rate	128-8192kbps
Bit Rate Type	CBR/VBR
S/N Ratio	>50DB
Image enhancement	Auto White Balance, Backligh compensation, Brighness, Contrast, Saturation adjusted
Subtitles	Support channel name,date/time
Flip Config	Up/down, Left/righ
Audio/Alarm	
Audio	Support the microphone input and Line out, support two-way voice intercom equipment
Equipment	An external audio equipment
Audio input/output	one channel audio input, one channel audio output
Audio Compression	G.711/G.726
Alarm input/output	one channel alarm input, one channel alarm output
Alarm way	Motion Detection: Configure motion area, detecting sensitivity is adjustable Cover alarm: the alarm sensitivity is adjustable
Alarm Processing	The control center to monitor, Go to PTZ preeset pos, send E-mail, Log record, SD card storage etc.
Network	
Protocol	HTTP、TCP/IP、UDP、SMTP、DDNS、DNS、SNTP、DHCP、FTP、RTP、RTSP、UPNP、ONVIF、28181
Ethernet	Ethernet (10/100 Base-T),RJ-45 connector
Safety	IP address filtering, User level password protection, The user access log
Softwre	
Web Browser	Microsoft Internet Explorer 6.0 and above, google、firefox etc.
Software Management	CMS and the devices compatible with ONVIF
Software intelligence function	Motion detection, Miss object detection, Moving object tracking, counting, Retrograde motion detection, etc.
Event action	Files are stored to the back end equipment, Send E-mail、Send SMS、Zoom in alarm、Pop ap map、Go to PTZ preset pos
Mobile Phone	Support iPhone, Android, Bit rate:32k-512k adjustable, Frame rate:6-12fps
Remote Access	DDNS, Software, P2P
Physical Properties	
Accessories	Power adapter, Network cable, Stand, Operation manual, CD, Screw bag
Power Comsumption	DC 12V, Module power consumption is less than 2W
Temperature	-20°C - 60°C
Humidity	10% - 80%
Certification	CE,FCC
Product specification are subject to change without notice	
www.winsafecctv.com	