

600TVL White Light Car License Plate Capture Camera



Features

- ※ Color 600TVL Hi Resolution
- ※ 5~60mm Auto Iris Lens
- ※ Available distance:1~40M
- ※ Separate glass: no Light diffusion and fog
- ※ Full Function OSD Menu
- ※ RS-485 Light Brightness Controllable
- ※ Light Value Can be Saved Permanently
- ※ Shutter Speed 1/50~1/120,000 Adjustable
- ※ Built-in FAN&HEATER, Operation Temperature-40℃~+60℃
- ※ DC12V Power Input
- ※ It Can Keep Stable Work Under Any Climate
- ※ Recognize No. Plate With Clarity at Any Vehicle Speed
- ※ IP65 Water-Proof

Specification

Model No.	WS-CL001WLN	WS-CL001WLP
Sensor	1/3" SONY Super HAD CCD	
Pixel	768(H) x 494(V)	752(H) x 582(V)
Scanning	2:1 Interlaced	
Sync. Mode	Internal, Line Lock	
Horizontal Frequency	15.734kHz	15.625kHz
Vertical Frequency	59.94Hz	50.00Hz
Resolution	600TVL Lines Horizontally(Color)/650TV Lines Horizontally(B&W)	
Video Output	1.0Vp -p/75Ω Video,0.714Vp-p Composite,0.286Vp-p	
Burst Level	0.286Vp-p	
S/N Ratio	54dBMin.(AGC Correct OFF)	
illumination	0.1Lux at F1.2(Color Mode)/0.001Lux at F1.2(B/W Mode)	
AGC	ON/OFF Optional	
Iris Control	DC AUTO IRIS(Shutter speed 1/50 - 1/120000)ELC	
E-Shutter	1/60-1/60,000S	1/50 - 1/50,000S
White Balance	ATW/AWC/MANUAL Selectable	
Backlight Compensation	OFF/LOW/MID/HIGH Selectable	
Motion Detect Alarm	ON/OFF(4 Areas for setting)	
Privacy Zone Masking	ON/OFF(4 Areas for setting)	
D/N Mode	AUTO/COLOR/B&w External Signal Control	
Communication	RS485, PELCO D/P	
Control Manner	Built-in OSD Menu	
Lens	KAWADEN Lens:f=6.0 - 50mm,F=1:1.4 ICR DC Auto IRIS	
Power Supply	12V DC	
Power Consumption	5W(DC)	
Size	143(W) x 166(H) x 290(L) mm	
Storage Temperature	-40 ℃ - +60℃	
Operation Temperature	- 40 ℃ - +60℃	
Humidity Range	20%-90%	
Weight	1000g	

※※※Product specification are subject to change without notice ※※※

www.winsafecctv.com