

HIGH DEFINITION LECTURER TRACKING PTZ CAMERAS





Order Models:

LT03: up to 1080p, 20X, Component interface

LT03-S: up to 1080p, 20X, HD-SDI interface

Dimensions



Accessories



Tripod
(Stand Mount)



Pole Bracket
(Ceiling Mount)

Specifications

- ※1080P HD zoom module,20x optical zoom;
- ※ With advanced image algorithm to detect and track moving object, excellent tracking performance with high stability;
- ※Automatically Lock-N-Track moving object, any change of light, object's gesture, interference of other moving object, or video playing from projector will not affect the tracking effect;
- ※Smooth tracking performance, no shaking image;
- ※With smooth and soft auto zooming function,always keep the object in the center of image with appropriate size;
- ※Support Pelco D protocol
- ※Smart AE technology to effectively avoid the interference of complicated lights from projectors,monitors etc;
- ※Anti projection interference;
- ※Easy to set effective tracking area and other value;
- ※Easy and simple installation, debugging and operation;
- ※Remote firmware upgrade via RS485.

Specifications

Model	WS-LT03	WS-LT03-S
HD Signal Format	1080p/30,1080p/29.97,1080p/25,1080i/60,1080i/59.94,1080i/50,720p/60,720p/59.94,720p/50,720p/30,720p/29.97,720P/25	
SD Signal Format	NTSC(CROP),NTSC(SQUEEZE),PAL(CROP),PAL(SQUEEZE)	
Image Sensor	1/2.8" Exmor CMOS Sensor	
Effective Pixel	3.27Megapixel	
Min.illumination	0.095 Lux(F1.6,ICR on)	

Synchronization	Internal	
BLC	ON/OFF	
Lens	f=4.1-73.8mm,F=1.4-F3.0	
Field of View	Wide 55.4 /Tele 2.9	
S/N Ratio	≥50dB	
P/T Range	Pan:340° ,Tilt:-30° ~90° auto flip	
P/T Speed	Pan Speed:0.1° -150° /sec,Tilt:0.1° -120° /sec	
Preset Number	64	
HD Video Output	Component(YPbPr)	HD-SDI
SD Video Output	CVBS	
Comm.Port	RS-485	
Baud Rate	9600bps	
Protocol	Pelco-D	
Operating Temperature	0° C--+50° C	
Storage Temperature	-20°C--+70° C	
Humidity	≤95%(non-condesation)	
Dimension(W X H X L)	160(D) x 206(H)mm	
Body Color	Black/White	
Product specification are subject to change without notice		