


NDI




## Features

- ※ 1/2.8" CMOS, 2.13mega pixel, 30x optical zoom
- ※ H.265, H.264 video compression, dual stream
- ※ Support NDI | HX output
- ※ IR/White lighting system, rang up to 60 meters
- ※ TF card for local storage
- ※ 10.8 - 28V voltage input
- ※ Auto power-off with low power supply
- ※ IP66 waterproof

## Dimensional Drawing



Front View



Bottom View

## Technical Specification

<b>Model No.</b>	<b>AC3-NS3003N</b>
<b>Camera</b>	
<b>Image Sensor</b>	1/2.8" Exmor CMOS, 2.13MP
<b>Active Pixel</b>	1920(H) x 1080(V)
<b>Video Standard(HD)</b>	1080p30,1080p/25,720p/60,720p50,720p/30,720p/25
<b>Signal System(SD)</b>	PAL/NTSC
<b>Min.Illumination</b>	Color: 0.0013Lux; B/W:0.0008Lux
<b>WB</b>	Auto
<b>Focus</b>	Auto/Manual

Exposure	Auto/Manual
S/N Ratio	Not less than 50dB
BLC	On/Off
WDR	On/Off
Digital Noise Reduction	1 - 5 Steps/Off
Digital Image Stabilization	No
D/N ICR	Auto/Manual
<b>Lens</b>	
Optical Zoom	30X
Digital Zoom	12X
Focal	f = 4.3mm - 129mm
IRIS	F1.6 - F3.5
View Angle	63.7°(H) - 2.3°(V)
<b>PTZ</b>	
Pan Range	360° Continuous
Pan Speed	Control Speed: 0.1° - 60°/s, adjustable; Preset Speed: 60°/s
Tilt Range	-15° - 90°(Auto Flip)
Tilt Speed	Control Speed: 0.2° - 60°/s, adjustable; Preset Speed: 60°/s
Preset	256
Preset Precision	±0.2°
<b>IR Light</b>	
Wave Length	850nm
Range	60m
Switch	Auto
<b>Network</b>	
Image Resolution	Max: 1920 x 1080@30fps
Image Compression	H.264, H.265
Audio Compression	AAC
Protocols	HTTP, RTSP, TCP, UDP, ONVIF
No. of User's Access	Up to 10
Dual Stream	Support
<b>Interface</b>	
Audio Interface	1 Line in, 1 Line out
Video Output(SD)	CVBS1.0Vp-p/75Ω, PAL or NTSC
Ethernet Interface	10/100M(NDI   HX)
Comm. Interface	RS-485
<b>General</b>	
OSD	English
Address	0 - 255
Comm. Protocol	Pelco-P/Pelco-D(Self-Adaptive)
Baud Rate	2400bps, 4800bps, 9600bps, 19200bps(Self-Adaptive)
Voltage	DC10.8 - 28V
Power	Min: 9W; Max:20W
Working Temperature	-25°C - 65°C
IP Index	IP66
Dimension	Φ136(mm) x 185(mm)
Weight	2.1Kg
<b>※※※ Product specification are subject to change without notice ※※※</b>	